

MULTIFILL-ELASTIC

DECLARATION OF PERFORMANCE

Declaration number: **MULTIFILL-ELASTIC / 2010-01**

1.Unique identification code of the product type	MULTIFILL-ELASTIC
2.Intended use/uses	Sealant for façade elements F-EXT-INT-CC (25LM) Sealant for sanitary joints XS1
3.Manufacturer	ISOMAT S.A 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece
4.Authorised representative	ISOMAT D.O.O. Prhovacka bb, 22310, Šimanovci, Serbia ISOMAT ROMANIA SRL Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania ISOMAT INTERNATIONAL E.O.O.D. Botevgradsko Shosse No.348. Sofia, Bulgaria ISOMAT GRADBENI MATERIALI D.O.O. Cvetkova ulica 2 9000 Murska Sobota, Slovenia ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI. ISTANBUL IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir ООО «ИЗОМАТ» 17, Nauchnyy proezd, building 15-3 117246, MOSCOW, Russian Federation ISOMAT DEUTSCHLAND GMBH Karl-Wirth-Strasse 14 D-76694 Forst,Germany
5.System/s of AVCP	System 3

6a.Harmonised standard	EN 15651-1:2012 EN 15651-3:2012
Notified body/ies	TECNALIA RESEARCH & INNOVATION NB 1292
6b.European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment body	Not relevant
Notified body/ies	Not relevant

7.Declared performance/s			
Essential characteristics	Performance	Test Method	Harmonized Technical Specification
Resistance to flow	≤ 3mm	EN ISO 7390	EN 15651-1:2012 EN 15651-3:2012
Loss of volume	≤ 10%	EN ISO 10563	
Determination of tensile properties	Pass	EN ISO 8339	
Determination of tensile properties (cold climate-CC)	Pass	EN ISO 8339	
Determination of tensile properties at maintained extension	No failure	EN ISO 8340	
Determination of tensile properties at maintained extension (cold climate-CC)	No failure	EN ISO 8340	
Determination of adhesion/cohesion properties at variable temperatures	No failure	EN ISO 9047	
Determination of tensile properties of sealants at maintained extension after immersion in water	No failure	EN ISO 10590	
Microbiological growth	0	EN ISO 846	
Durability	Pass		
Reaction to fire	Class E	EN 13501-1	
Release of chemicals	Compliance	See MSDS	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



Konstantinos Iliopoulos
Quality Manager



Georgios Syriopoulos
Certifications & Specifications Manager

Agios Athanasios 20 / 09 / 2022



Visit our website:

www.isomat.eu

ISOMAT S.A.
BUILDING CHEMICALS,
MORTARS & PAINTS
export@isomat.eu | www.isomat.eu

HEADQUARTERS
THESSALONIKI, GREECE
17th km Thessaloniki - Ag. Athanasios Road
P. O. BOX 1043, 570 03 Ag. Athanasios
T: +30 2310 576 000

