

ISOMAT SL-17

DECLARATION OF PERFORMANCE

Declaration number: **ISOMAT SL-17 / 1441-01**

1.Unique identification code of the product type	ISOMAT SL-17
2.Intended use/uses	Surface protection products- coating -ingress protection (1.3) -moisture control (2.2) -increasing resistivity (8.2)
3.Manufacturer	ISOMAT S.A 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece
4.Authorised representative	ISOMAT D.O.O. Prhovacka bb, 22310, Šimanovci, Serbia ISOMAT ROMANIA SRL Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania ISOMAT INTERNATIONAL E.O.O.D. Botevgradsko Shosse No.348. Sofia, Bulgaria ISOMAT GRADBENI MATERIALI D.O.O. Cvetkova ulica 2 9000 Murska Sobota, Slovenia ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI. ISTANBUL IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir ООО «ИЗОМАТ» 17, Nauchniy proezd, building 15-3 117246, MOSCOW, Russian Federation ISOMAT DEUTSCHLAND GMBH Karl-Wirth-Strasse 14 D-76694 Forst,Germany
5.System/s of AVCP	System 2+(for uses in buildings and civil engineering works)

6a.Harmonised standard	EN 1504-2:2004
Notified body/ies	BUILDING RESEARCH INSTITUTE-NISI NB 2032
6b.European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment body	Not relevant
Notified body/ies	Not relevant

7.Declared performance/s			
Essential characteristics	Performance	Test Method	Harmonized Technical Specification
CO₂ permeability	Sd > 50m	EN 1062-6	EN 1504-2:2004
Water vapour permeability	Class I (permeable)	EN 7783-2	
Capillary absorption	$w < 0,1 \text{ kg/m}^2 \text{ h}^{0,5}$	EN 1062-3	
Adhesion	$\geq 1,0 \text{ MPa}$	EN 1542	
Reaction to fire	Class F	EN 13501-1	
Dangerous substances	Complies with 5.3		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



Konstantinos Iliopoulos
Quality Manager



Georgios Syriopoulos
Certifications & Specifications Manager

Agios Athanasios 30/07/2022

CE MARKING

 2032
ISOMAT S.A. 17 th km Thessaloniki – Ag. Athanasios P.O. BOX 1043, 570 03 Ag Athanasios, Greece 18
2032-CPR-10.11 DoP No.: ISOMAT SL-17 / 1441-01 EN 1504-2 Surface protection products Coating Permeability to CO ₂ : Sd > 50 m Water vapor permeability: Class I (permeable) Capillary absorption: $w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$ Adhesion: $\geq 1.0 \text{ N/mm}^2$ Reaction to fire: Euroclass F Dangerous substances comply with 5.3



Visit our website:
www.isomat.eu

ISOMAT S.A.
BUILDING CHEMICALS,
MORTARS & PAINTS
export@isomat.eu | www.isomat.eu

HEADQUARTERS
THESSALONIKI, GREECE
17th km Thessaloniki - Ag. Athanasios Road
P. O. BOX 1043, 570 03 Ag. Athanasios
T: +30 2310 576 000

