

NANOPRO-M

DECLARATION OF PERFORMANCE

Declaration number: **NANOPRO-M / 1421-02**

1.Unique identification code of the product type	NANOPRO-M
2.Intended use/uses	Surface protection products- hydrophobic impregnation -ingress protection (1.1) -moisture control (2.1) -increasing resistivity (8.1)
3.Manufacturer	<i>ISOMAT S.A</i> 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece
4.Authorised representative	<i>ISOMAT D.O.O.</i> Prhovacka bb, 22310, Šimanovci, Serbia <i>ISOMAT ROMANIA SRL</i> Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania <i>ISOMAT INTERNATIONAL E.O.O.D.</i> Botevgradsko Shosse No.348. Sofia, Bulgaria <i>ISOMAT GRADBENI MATERIALI D.O.O.</i> Cvetkova ulica 2 9000 Murska Sobota, Slovenia <i>ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI.</i> <i>ISTANBUL</i> IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir <i>ООО «ИЗОМАТ»</i> 17, Nauchniy proezd, building 15-3 117246, MOSCOW, Russian Federation <i>ISOMAT DEUTSCHLAND GMBH</i> Karl-Wirth-Strasse 14 D-76694 Forst,Germany
5.System/s of AVCP	System 4

6a.Harmonised standard	EN 1504-2:2004
Notified body/ies	Not relevant
6b.European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment body	Not relevant
Notified body/ies	Not relevant

7.Declared performance/s			
Essential characteristics	Performance	Test Method	Harmonized Technical Specification
Depth of penetration	Class 1<10mm	EN 14630	EN 1504-2:2004
Water absorption and resistance to alkali	Absorption ratio <7,5% compared with the untreated specimen	EN 13580	
Water absorption and resistance to alkali	Absorption ratio <10% after immersion in alkali	EN 13580	
Drying rate coefficient	Class II>10%	EN 13579	
Dangerous substances	Complies with 5.3	EN 1504-2	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



Konstantinos Iliopoulos
Quality Manager



Georgios Syriopoulos
Certifications & Specifications Manager

Agios Athanasios 30 / 07 / 2022

CE MARKING



ISOMAT S.A.

17th km Thessaloniki – Ag. Athanasios
P.O. BOX 1043, 570 03 Ag Athanasios, Greece
12

EN 1504-2

DOP No. NANOPRO-M/1421-02

surface protection products

hydrophobic impregnation

Depth of penetration: Class I < 10 mm

Water absorption and resistance to alkali:

Absorption ratio <7,5% compared with the
untreated specimen,

Absorption ratio <10% after immersion
in alkali solution

Drying rate: Class II > 10%

Dangerous substances comply with 5.3



Visit our website:
www.isomat.eu

ISOMAT S.A.
BUILDING CHEMICALS,
MORTARS & PAINTS
export@isomat.eu | www.isomat.eu

HEADQUARTERS
THESSALONIKI, GREECE
17th km Thessaloniki - Ag. Athanasios Road
P. O. BOX 1043, 570 03 Ag. Athanasios
T: +30 2310 576 000

